








AELIAN
PORTABLE UNITS
 2 Cooling models
 From 2.64 kW to 3.5 kW



PRODUCT ADVANTAGES

- Particularly suited for residential and light commercial air conditioning needs.
- Auto swing, sleep function.
- Self diagnostic and overflow protection.
- Memory from power failure.
- High dehumidification capacity.
- Low noise levels in the units.
- 3 fan speed.
- Easy installation (no specific requirements) and service.
- Easy access to the connecting hose to exhaust air out.
- Two options to control the unit by touch panel (built-in) or by wireless remote controller.
- Touch pad on the unit.
- Infrared remote control with liquid crystal display.
- Moving wheels for more convenience.



		AELIAN 009	AELIAN 012
Cooling	Capacity	2.64	3.5
	Power input	1.1	1.34
	EER/Energy Label	2.6/A	2.6/A
Indoor unit	Type	Monobloc	Monobloc
	Sound pressure level 1 mt ¹	54/50/48	56/54/50
	Airflow ²	420/390/300	450/420/390
	Dehumidification	1.2	1.50
	Dimensions (H/M/L)	450x400x840	500x460x840
	Weight	34	45
Part number		7MB021052	7MB021053
Power supply 1-230V - 50Hz			

¹Data are relative to Low speed, Medium speed and High speed

²Data are relative to High speed