

Wall mounted unit

AC fan motor unit for wall mounting

- › High aesthetic cabinet design
- › Optimum air distribution
- › Easy to install
- › Wireless remote control up to 9 m distance
- › 3-speed fan motor
- › Wide operating range
- › Low operating sound level thanks to tangential fan
- › Insulated with self-extinguishing class 1 heat insulation
- › Removable washable air filter (self-extinguishing class 1)



More details and final information
can be found by scanning or
clicking the QR codes.



FWT-GT

Indoor unit			FWT-GT	02	03	04	05	06		
				2-pipe						
Cooling capacity (standard conditions)	Total capacity	High kW	2.40	2.67	3.27	4.49	5.21			
		Medium kW	2.20	2.23	2.79	4.02	4.32			
		Low kW	1.94	2.02	2.52	3.76	4.04			
	Sensible capacity	High kW	1.82	1.99	2.60	3.38	4.03			
		Medium kW	1.73	1.69	2.21	3.00	3.52			
		Low kW	1.50	1.49	1.91	2.77	3.22			
Heating capacity (standard conditions)	High kW	2.71	2.96	3.71	5.07	6.23				
	Medium kW	2.41	2.62	3.29	4.51	5.38				
	Low kW	2.06	2.25	2.75	4.03	4.83				
Power input	High kW	0.031	0.032	0.042	0.053	0.072				
	Medium kW		0.03	0.04	0.05	0.07				
	Low kW		0.03		0.04	0.06				
FCEER				D			C	D		
FCCOP					C					
Dimensions	Unit	HeightxWidthxLength	mm	288x800x206			310x1,070x224			
Weight	Unit		kg	9.00			14.0			
Casing	Colour			White						
Air filter	Type			Washable Saranet						
Fan	Type			Cross flow fan						
	Quantity			1						
Total sound power level	Air flow rate	High m ³ /h	442	476	629	866	1,053			
		Medium m ³ /h	391	425	544	765	883			
		Low m ³ /h	340	374	442	663	782			
Sound pressure level	High dBA	45.0	48.0		55.0		59.0			
	Medium dBA	41.0	44.0		50.0		54.0			
	Low dBA	36.0	39.0		45.0		51.0			
Piping connections	Drain OD mm				19					
	Power supply Phase/Frequency/Voltage Hz/V			1N~/50/220-240						
	Control systems Infrared remote control			WRC-HPC						
	Wired remote control			MERCA / SRC-HPA						

For standard conditions refer to the Measuring Conditions table, at the end of this catalogue